

General Disclaimer

One or more of the Following Statements may affect this Document

- This document has been reproduced from the best copy furnished by the organizational source. It is being released in the interest of making available as much information as possible.
- This document may contain data, which exceeds the sheet parameters. It was furnished in this condition by the organizational source and is the best copy available.
- This document may contain tone-on-tone or color graphs, charts and/or pictures, which have been reproduced in black and white.
- This document is paginated as submitted by the original source.
- Portions of this document are not fully legible due to the historical nature of some of the material. However, it is the best reproduction available from the original submission.

1, C.E. Chassay SE4

TO: B. French/W. E. McAllum, SE4	DATE: 6, 11/13/81
FROM: G.W. Belshaw, Project Engineer	CONTRACT: NAS9-15629 5.
SUBJECT: Life Sciences Passive GN ₂ Freezer Thermal Performance Test Summary 2.	

NASA-CR-167546

SUMMARY

The purpose of this report is to summarize the thermal performance testing that has been conducted on the Life Sciences Passive GN₂ Freezer project as well as discuss the improvements to the freezers to improve the thermal performance of the containers.

Procedures were developed, based upon these tests, to initially charge the freezers with LN₂ and verify that the freezer performance will be adequate for the mission duration.

Improvements were made to the Corvac sample tube to limit the amount of breakage due to thermal expansion of the liquid during freezing.

A method of verifying the freezer vacuum insulative integrity was defined as well as a procedure for refurbishment of the internal vacuum level. Freezer modifications were made to ease the re-evacuation of the containers.

It was also determined that the orientation of the freezer in a 1-G environment, after being charged, had to remain in a vertical position. The LN₂ boiloff rate increased significantly in a horizontal position. This resulted in a stowage definition in the spacecraft prior to launch.

Functional testing, using the SL-1 mission timeline showed that the freezer will maintain samples in the frozen state for the duration of the mission.

In general, confidence has been established that the passive GN₂ freezer performance is consistent, predictable and will satisfy the mission requirements.

INTRODUCTION

The Life Sciences Passive GN₂ freezer is constructed by Cryogenics Associates (CA) of Indianapolis, Indiana. Four (4) freezers received from CA have been utilized in the testing and evaluation.


The passive GN₂ freezer, as shown in the sketch of Figure 1, is a vacuum insulated container with an inner container lined with a calcium silicate absorbant material. The screw-on cap contains a urethane foam neck plug to reduce heat leakage through the cap.

N82-19809

(NASA-CR-167546) LIFE SCIENCES PASSIVE GN₂
FREEZER THERMAL PERFORMANCE TEST SUMMARY
Report (General Electric Co.) 79 P
HC A05/MF A01

Unclas
09247
G3/51

CSC 06C



GENERAL ELECTRIC

Charging of the freezer is accomplished by filling the center container with LN₂. As the LN₂ boils, the container is maintained full for a period of 24 hours. During this period, approximately 12 pounds of LN₂ is absorbed by the calcium silicate.


At the end of the charging period, the LN₂ in the center cylinder is poured out of the container, leaving the center cylinder dry. The absorbed LN₂ will then boiloff at a constant rate, based upon the amount of heat leakage into the container, maintaining the internal cylinder temperature at approximately LN₂ temperature (-195°C, -230°F).

The LN₂ boiloff rate can be easily determined by measuring the weight loss of the container with time.

During the time period between February, 1980 and the present, a total of six (6) tests were conducted on the containers. Table 1 presents a summary of the testing configurations and general results. All units, with the exception of one, were tested more than once.

The following are copies of the original test reports for the six tests conducted. They provide the details of each test, samples used, and test results.


George W. Belshaw



LIFE SCIENCES PASSIVE GN₂ FREEZER

FIGURE 1

LIFE SCIENCES PASSIVE GN₂ FREEZER TEST SUMMARY

TEST NO.	DATES	SERIAL NO.	TEST DURATION (HRS)	BNLOFF RATE (#/HR)	NO. OF SAMPLES	LOCKER USED	SAMPLE HOLDER USED	EXPERIMENT HOLDER USED	INITIAL DRY WEIGHT
1	2/26/80 - 3/6/80	1358-79	200	.045	36	NO	NO	NO	# 14.06
2	11/17/80 - 11/26/80	1359-79	200	.054	36	NO	NO	NO	# 13.625
3	12/1/80 - 12/12/80	987-80	200	.064	6+ESA	NO	-	YES	# 14.42
		988-80	216	.050	36	NO	YES	-	# 14.52
4	1/27/81 - 2/17/81	988-80	312	.046	NO	NO	NO	NO	# 14.52
5	2/26/81 - 3/9/81	988-80	144	.049	6+ESA	YES	-	YES	# 14.52
6	8/10/81 - 9/2/81	1358-79	336	.044	NO	NO	NO	NO	# 14.21
		1359-79	144	.045	6+ESA	NO	-	YES	# 13.86

TABLE 1

TO: D. R. White, SE4	DATE: 8/12/80
FROM: G.W. Belshaw, Project Engineer	CONTRACT: NAS9-15629
SUBJECT: Life Sciences GN ₂ Passive Freezer Thermal Performance Test Report	

Enclosed are four (4) copies of Test Report No. PETX177 documenting the testing performed at JSC to evaluate the thermal performance under a simulated mission timeline condition of the Cryogenic Associates Model SD-404-P GN₂ Passive Freezer.


George W. Belshaw

LIFE SCIENCES GN₂ PASSIVE FREEZER

THERMAL PERFORMANCE TEST

GENERAL  ELECTRIC

SPACE DIVISION

HOUSTON, TEXAS

UNDER CONTRACT: NAS9-15629

REPORT NO. PETX177

LIFE SCIENCES GN₂ PASSIVE FREEZER

PERFORMANCE TEST REPORT

AUGUST, 1980

Prepared by:



George W. Belshaw
Project Engineer
General Electric Company

Under contract: NAS9-15629

SUMMARY

This report provides the results of testing performed at NASA Johnson Space Center (JSC) to evaluate the thermal performance of the Cryogenic Associates Model SD-404-P GN₂ freezer. Results indicate that the freezer will provide freezing capability for an eight day period for the sample insertions timeline investigated. Significant sample breakage did occur due to thermal expansion during freezing and should be investigated further.

PURPOSE

The purpose of the testing was to evaluate the thermal performance of the Cryogenic Associates (CA) Model SD-404-P GN₂ freezer under simulated mission timeline conditions. All prior testing had been done with the freezer empty and the passive freezer life is reduced by the insertion of samples to be frozen.

It was required to determine the freezer life maintaining the internal temperature below -10°C (14°F) with insertion of samples into the freezer.

TEST CONFIGURATION AND SET UP

Two (2) freezers were received by JSC from CA (Serial numbers 1358-79 and 1359-79). Both containers had been tested empty by CA prior to shipment and these test reports are presented in Figures 1 and 2.

The unit to be tested at JSC was 1358-79. Two thermocouples were inserted through the cover and located as shown in Figure 3.

Thirty six (36) 15 ml Venoject vacuum blood collection tubes, filled with a water/sodium heparin solution were utilized for the test. These tubes were filled to a level as shown in Figure 4.

The freezer test timeline to be utilized is shown in Figure 5. Three sample insertion periods were established to include 12 samples at approximately

24 hours, 6 samples at approximately 72 hours and then 18 samples at approximately 144 hours. These samples were to be placed in plastic bags and inserted into the freezer.

The freezer container was placed on a scale and the weight of the freezer was monitored throughout the test period. An initial container dry empty weight of 14.06# was recorded.

The freezer was then filled with LN_2 and allowed to stand. During the charging period it was required to maintain the LN_2 level for a period of approximately 24 hours. This would allow for the absorbant material in the freezer to become charged with LN_2 .

The level of LN_2 within the freezer was maintained at a level approximately 2" below the fill level for the period.

The LN_2 was poured out at 0900 2/26/80 and the weight was recorded at 25.75#. This weight is .36# less than that recorded by CA during their testing (Figure 1) and was due to the low level of LN_2 within the freezer during the charging period.

TEST RESULTS

During the testing period the freezer internal temperature and total weight was monitored at regular intervals.

Testing began at 0900 2/26/80 with internal temperatures at -314°F (-192°C) and -308°F (-189°C). The initial weight was 25.75#.

Figure 6 presents the temperature-time history of the freezer during the testing period. Figure 7 presents the freezer total weight of the freezer during the period.

At 0912 2/27/80 (24 hr) 12 room temperature samples were placed in a plastic bag and this weight recorded at .821#. The freezer was opened and the samples placed into the freezer. Figure 8 presents the thermal response of the internal portion of the freezer during this period. It should be noted that when the freezer was opened the thermocouples had to be removed also. The internal temperature returned to LN_2 temperature level after approximately 2 hours. The freezer remained open for a period of approximately 2 minutes.

Again at 0920 (72.5 hrs) 2/29/80 the freezer was opened and 6 samples of weight .39# was inserted into a bag containing the original 12 samples. The first 12 were removed and all 18 were placed in a new plastic bag due to breakage of the first bag. At LN_2 temperature the plastic bag is extremely fragile and was destroyed upon removal. The freezer remained open for a period of 2 minutes during this period. Figure 9 presents the temperature response during this insertion period and the freezer recovery.

At 0833 3/3/80 (143 hours) the freezer was again opened and 18 additional samples of weight 1.21# were placed in a plastic bag and inserted into the

freezer above the original 18. This insertion almost completely filled the internal portion of the freezer. As before, the insertion period was approximately 2 minutes and the thermal recovery is shown in Figure 10.

Thermal decay began to occur at approximately 1400 3/4/80 (170 hours) at which point the freezer weight was 16.875# or approximately 5 oz of LN_2 remaining. Temperatures continued to rise as shown in Figure 11 until the test was terminated at 1700 3/5/80 (200 hours) with the freezer internal temperatures ranging between -8°F and -25°F (-22°C and -32°C).

It was estimated that the testing limits would be reached within 2 hours after termination of testing and would result in a total decay time of 32 hours.

The container remained closed until 0830 3/7/80 at which time the samples, now completely thawed, were removed.

Upon removal of the plastic bags, there were several samples that were broken. Each bag contained 18 samples and the upper bag had seven (7) unbroken tubes. The lower bag had only two (2) unbroken tubes.

This breakage was due to the thermal expansion of the liquid during freezing.

CONCLUSIONS

The CA GN_2 freezer maintained temperatures of 36 samples below test limits for a period of approximately 200 hours. If the initial charging had been to

the 26.11# level instead of 25.75#, the time would be extended by approximately 8 hours since the static boiloff rate was calculated to be $\dot{0.045}$ #/hr which remained fairly consistent throughout the testing.

The breakage of the sample tubes needs to be investigated and sample tubes need to be utilized that will withstand the LN_2 temperature and the rapid freezing rates.

ORIGINAL PAGE IS
OF POOR QUALITY

REC'D 12/18/79

CRYOGENIC ASSOCIATES

6565 Colfman Road
Post Office Box 68443
Indianapolis, Indiana 46268

CA 407-19

MODEL # SD-404-P

EMPTY WEIGHT 14.04

SERIAL # 1358-79 JSC TEST UNIT 408

EVAPORATION RATE 468 LBS/LDAY

DATE	TIME	WEIGHT	REMARKS
11-27-79	2:36 P	31.22	3 1/2" Dia. Boze is Full
11-27-79	5:00 P	26.11	Boze Dumped 11.89 Kgs
11-28-79	7:04 A	25.63	$\frac{.48}{14.06} = .019\%/DAY = .46\%/DAY = 14.73\ DAYS$
11-28-79	1:10 P	25.38	$\frac{.69}{24.266} = .028\%/DAY = .494\%/DAY = 13.72\ DAYS$
11-29-79	7:20 A	24.74	$\frac{.87}{23.666} = .037\%/DAY = .495\%/DAY$
11-30-79	7:00 A	23.87	$\frac{.87}{23.666} = .037\%/DAY = .495\%/DAY$
12-3-79	7:05 A	21.38	$\frac{2.49}{72.05} = .024\%/DAY = .465\%/DAY$
12-4-79	7:40 A	20.46	$\frac{.92}{24.583} = .037\%/DAY = .504\%/DAY$
12-5-79	7:13 A	19.60	$\frac{.86}{23.550} = .037\%/DAY = .492\%/DAY$
12-6-79	7:55 A	18.69	$\frac{.91}{24.700} = .037\%/DAY = .496\%/DAY$
12-6-79	5:00 P	18.34	$\frac{.35}{9.083} = .038\%/DAY = .519\%/DAY$ END OF 10 DAY TEST.

CUSTOMER NASA

D. Fish

TYPE OF INSULATION SUPER INSULATION

NUMBER OF WRAPS 45

WITNESS:

METHOD APPLIED

TRUNION No

EVALUATION PROCEDURE 1 DAY RAINING 3 DAY

Acc Pump

12-7-79	8:30 A.M.	17.80	$\frac{.034\%/hr}{.019\%/hr} = .469\%/DAY$
12-10-79	7:15 A.M.	15.27	$\frac{.035\%/hr}{.020\%/hr} = .481\%/DAY$
12-10-79	4:46 P.M.	14.95	
12-11-79	8:18 A.M.	14.37	$\frac{.58}{15.533} = .037\%/hr = .869\%/DAY = .503\%/DAY$
12-11-79	2:50 P.M.	14.18	EMPTY

FIGURE 1

REC'D 12/18/79

CRYOGENIC ASSOCIATES

6565 Coffman Road
Post Office Box 68443
Indianapolis, Indiana 46268

WEIGHT OF BLOOD TUBE RACKING
DEVICE & SPACER — 391 gms.
FOR RAY HANCOCK 2/15/80

CA 407-19

MODEL # SD-404-P

SERIAL # 1359-79

EMPTY WEIGHT 13.82

EVAPORATION RATE .480 AVG 1/Day

DATE	TIME	WEIGHT	REMARKS	ORIGINAL PAGE IS OF POOR QUALITY
11-26-79	2:35pm	31.61	3.5" DIA. BORE IS FULL	
11-27-79	5:02p	25.47	DUMPED BORE	11.58
11-28-79	7:02 A	24.92	$\frac{5.5}{14.00} = .942\%/DAY = .52\%/DAY$	12.37 DAYS
11-28-79	1:11P	24.68	$\frac{.86}{24.316} = .848\%/DAY = .476\%/DAY$	13.7 DAYS
11-29-79	7:21 A	24.06	$\frac{.86}{23.650} = .872\%/DAY = .490\%/DAY$	
11-30-79	7:00 A	23.20	$\frac{2.53}{72.116} = .841\%/DAY = .473\%/DAY$	
12-3-79	7:07 A	20.67	$\frac{.86}{24.550} = .840\%/DAY = .472\%/DAY$	
12-4-79	7:40A.	19.81	$\frac{.86}{23.550} = .876\%/DAY = .492\%/DAY$	
12-5-79	7:13A	18.95	$\frac{.90}{24.700} = .874\%/DAY = .491\%/DAY$	
12-6-79	7:55A	18.05	$\frac{.30}{9.083} = .792\%/DAY$	TEST CONDUCTED BY: .445%/DAY END OF 10 DAY TEST
12-6-79	5:00P.	17.75		

CUSTOMER NASA

Delta Fish

TYPE OF INSULATION SUPER INSULATION

NUMBER OF WRAPS 45

WITNESS:

METHOD APPLIED


TRUNION No

EVALUATION PROCEDURE 1 DAY RUSHING 3 DAY

Diff. Pump

12-7-79	8:25 A.M.	17.21	.034%/hr	.019%/hr	.469%/DAY
12-10-79	7:21 A.M.	14.70	.035%/hr	.019%/hr	.477%/DAY
12-10-79	4:46 P.M.	14.37			
12-11-79	8:19 A.M.	13.93	$\frac{.44}{15.550} = .028\%/hr$.679%/DAY	.381%/DAY
12-11-79	2:50 P.M.	13.82	EMPTY		

FIGURE 2




PASSIVE GN₂ FREEZER TEST CONFIGURATION

ORIGINAL PAGE
BLACK AND WHITE PHOTOGRAPH



FIGURE 4

-195°C PASSIVE GN₂ FREEZER SAMPLE INSERTION TIMELINE



NOTES:

- ① Prepare freezer for test start
- ② Test Start 0900 Tuesday - LN₂ poured off and weight recorded
- ③ 12 Glass tubes inserted at 0915 Wednesday (Sample # 1)
- ④ 6 Glass tubes inserted at 0920 Friday (Sample # 2)
- ⑤ 18 Glass tubes inserted at 0830 Monday (Sample # 3)
- ⑥ Continue test until inside temperature reaches -10°C (14°F)

FIGURE 5

ORIGINAL PAGE IS
OF POOR QUALITY

PASSIVE GN₂ FREEZER THERMAL RESPONSE

NOTE: DETAILED RESPONSE OF
SAMPLE IN REACTION AND
THERMAL DERIVATIVE IN SEPARATE
FIGURES

THERMOCOUPLE 1 DATA
PLOTTER

TEMPERATURE - °F

TEST UNIT
100 (MAY)

INTERPOL 2

INTERPOL 1

INTERPOL 3

INTERPOL 4

TIME - HOURS


0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79	80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95	96	97	98	99
---	---	---	---	---	---	---	---	---	---	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

FIGURE 6


ORIGINAL
PAGE 14


10 X 10 TO THE CM. 359.14
KEUTTEL & ESSER CO. NEW YORK, N. Y.

ORIGINAL PAGE IS
OF POOR QUALITY




ORIGINAL PAGE IS
OF POOR QUALITY





ORIGINAL PAGE IS
OF POOR QUALITY






FIGURE 11

G. A. B. S. H. A. W.
3-6-80

TO: B. French, SE4	DATE: 12/1/80
FROM: G.W. Belshaw, Project Engineer	CONTRACT: NAS9-15629
SUBJECT: GN ₂ Passive Freezer Thermal Test, November, 1980	

Enclosed are the results of the thermal testing of the GN₂ Passive Freezer (serial no. 1359-79) conducted from November 17-26, 1980.

Results indicate a static boiloff rate of approximately .05 #/hr. The test was terminated 184 hours after LN₂ pour-off, which was four hours after landing on the mission timeline. The samples removed at this time were still frozen. Four samples were cracked, however, the breakage rate was significantly reduced from previous testing by using the tempered, wrapped tubes.

Also included is a curve representing the initial testing by Cryogenics Associates in November, 1979. This test indicated a static boiloff rate of .036 #/hr.


George W. Belshaw

GN₂ PASSIVE FREEZER TEST PROCEDURES

UNIT TO BE TESTED: Cryogenics Associates S/N 1359-79

11/17/80

- ° Record container weight with cover.
Note: All weights to include cover in place.

Prior to 4 pm

- ° Begin filling with LN₂ - continue until container is full
- ° Record container weight

Every 1-2 hours as needed

- ° Refill container with LN₂ to maintain level within one inch of top
- ° Record container weight after each topping.

11/18/80

- ° Continue topping off and recording weight.

4 pm

- ° Pour-off LN₂ from container
- ° Replace cover
- ° Record container weight

Every 2-3 hours


- ° Record container weight until end of test

End of test when internal temperature reaches -10°C (14°F)

Est. at 11/28/80

GN₂ PASSIVE FREEZER TEST PROCEDURES

- [illegible]




PASSIVE GN₂ FREEZER
SL-1 TEST TIMELINE

SAMPLE CONTAINER

NOVEMBER 1980


7-570117-1 SERIAL NO. 1359-77

CONTAINER TOTAL WEIGHT 13.225



大正十一年

ORIGINAL PAGE IS
OF POOR QUALITY



11-26-80

CHECK OF CORVAC TUBES UPON REMOVAL FROM
FREEZER - 0830 11-26-80

- SAMPLE INSERTION #1 - stowed freezer bottom
15ml tubes - none cracked
Tube numbers 7, 8, 12, 15, 22, 26, 27, 28, 33, 36

10ml tubes - Tube no. 49 cracked
43 OK

- SAMPLE INSERTION #2

Small bag - stowed freezer bottom
15ml tubes - Tube no. 5 cracked
Tube no.'s 6, 9, 29 OK

10ml tubes - Tubes 38, 46 both cracked

Large bag - stowed freezer upper

15ml tubes - Tube no. 2 - cracked

Tube no.'s 1, 3, 10, 13, 16, 17, 18, 19, 20, 21, 23,
24, 25, 30, 32, 35 OK

REC'D 12/18/79

CRYOGENIC ASSOCIATES

6565 Collman Road
Post Office Box 68443
Indianapolis, Indiana 46268

WEIGHT OF BLOOD TUBE RACKING
DEVICE & SPACER - 391 gms.
FOR RAY HANCOCK 2/15/80

CA 407-19

MODEL # SD-404-P

SERIAL # 1359-79

EMPTY WEIGHT 13.82

EVAPORATION RATE .460 AVE 1/0AY

ORIGINAL PAGE IS
OF POOR QUALITY

DATE	TIME	WEIGHT	REMARKS	
11-26-79	2:35 PM	31.61	3.5" DIA. BORE IS FULL	
11-27-79	5:02 P	25.47	DUMPED BORE	11.58
11-28-79	7:02 A	24.92	$\frac{5.5}{14.00} = .942\%/\text{DAY} = .52\%/\text{DAY}$	12.37 DAYS
11-28-79	1:11 P	24.68	$\frac{86}{24.316} = .848\%/\text{DAY} = .476\%/\text{DAY}$	13.7 DAYS
11-29-79	7:21 A	24.06	$\frac{86}{23.650} = .872\%/\text{DAY} = .490\%/\text{DAY}$	
11-30-79	7:00 A	23.20	$\frac{2.53}{72.116} = .841\%/\text{DAY} = .473\%/\text{DAY}$	
12-3-79	7:07 A	20.67	$\frac{86}{24.550} = .840\%/\text{DAY} = .472\%/\text{DAY}$	
12-4-79	7:40 A	19.81	$\frac{86}{23.550} = .876\%/\text{DAY} = .492\%/\text{DAY}$	
12-5-79	7:13 A	18.95	$\frac{86}{24.700} = .874\%/\text{DAY} = .491\%/\text{DAY}$	
12-6-79	7:55 A	18.05	$\frac{30}{9.083} = .792\%/\text{DAY}$	
12-6-79	5:00 P	17.75	TEST CONDUCTED BY: = .445%/\text{DAY} END OF 10 DAY TEST	

CUSTOMER NASA

A. Fish

TYPE OF INSULATION SUPER INSULATION

NUMBER OF WRAPS 45

WITNESS:

METHOD APPLIED


TRUNION No

EVALUATION PROCEDURE 1 DAY RUSHING 3 DAY

Diff. Pump

12-7-79	8:25 A.M.	17.21	.034%/hr	.019%/hr	.469%/DAY
12-10-79	7:21 A.M.	14.70	.035%/hr	.019%/hr	.477%/DAY
12-10-79	4:46 P.M.	14.37			
12-11-79	8:19 A.M.	13.93	$\frac{.44}{15.550} = .028\%/\text{hr} = .679\%/\text{DAY} = .381\%/\text{DAY}$		
12-11-79	2:50 P.M.	13.82	EMPTY		

ORIGINAL PAGE IS
OF POOR QUALITY



TO: B. French, SE4	DATE: 1/6/81
FROM: G.W. Belshaw, Project Engineer	CONTRACT: NAS9-15629
SUBJECT: GN ₂ Passive Freezer Thermal Test - December, 1980	

Enclosed are the results of the GN₂ Passive Freezer thermal testing conducted from December 1-12, 1980. These tests were conducted with two containers received from Cryogenics Associates (CA) and followed the SL-1 mission timeline.


The two containers tested were designated container "A" (CA serial no. 988-80) and container "B" (CA serial no. 987-80). The static boiloff rates for these two containers were approximately .05 #/hr for container "A" and .064 #/hr for container "B".

A significant difference was noted from the previous testing in the amount of LN₂ absorbed by the container during the 24 hour charge period. The November, 1980 test (CA serial no. 1359-79) absorbed 11.84# of LN₂, while these containers absorbed 12.91# of LN₂ for container "A" and 12.875# of LN₂ in container "B". For this reason, even with the higher static boiloff rate of container "B", the mission timeline was easily completed.

Testing on container "A" was terminated at 214 hours with the removal of 36 frozen samples. Container "B" testing was completed at 184 hours (4 hours after landing) with the removal of the experiment holder containing 6 frozen samples and the ESA experiment simulation. Internal temperatures at this removal time were approximately -200°F and would have easily held for over 200 hours. Upon removal of the samples, it was noted that there was only one (1) cracked tube in container "B".

Major difficulties were encountered with the sample holder, in both retaining frozen tubes and accepting the proper number of tubes. Details of the problems encountered are included in the test comments.

Also included with this report are the mission timeline test procedures, the container weight loss, the container thermal response, comments on sample holder insertion and removal and experiment holder removal, recorded weights and temperatures recorded during the test period.


George W. Belshaw

GN₂ PASSIVE FREEZER TEST PROCEDURES
MISSION TIMELINE TEST

UNITS TO BE TESTED: "A" Serial No. 988-80
"B" Serial No. 987-80

12-1-80

- Record container weight "A" with cover
Note: All weights include cover in place

Prior to
4 pm

- Fill container "A" with LN₂ - continue until container is full
- Record container weight

Every 1-2 hrs
as needed

- Refill container "A" with LN₂ to maintain level within one inch of top.
- Record container weight after each topping

12-2-80

- Continue topping and recording weight

4 pm

- Pour off LN₂ from container, replace cover and record weight

Every 2-3 hours

- Record container weight until end of test

12-3-80

- Record container weight "B" with cover

Prior to
4 pm

- Fill container "B" with LN₂ - continue until container is full
- Record container weight

Every 1-2 hours
as needed

- Refill container "B" with LN₂ to maintain level within one inch of top
- Record container "B" weight after each topping

12-4-80

- Continue topping "B" and recording weight

4pm

- Pour off LN_2 from container "B", replace cover and record weight

Every 2-3 hours

- Record container weight until end of test.

End of test when internal temperature of both containers is above $-10^{\circ}C$ ($14^{\circ}F$)

Est. at 12/15/80

GN₂ PASSIVE FREEZER TEST PROCEDURES
MISSION TIMELINE TEST

• SAMPLE INSERTION #1 - CONTAINER "A"

(THURS) 9:15am 12-4-80

10 - 15ml Corvac Samples
2 - 10ml Corvac Samples

• RECORD WEIGHT OF SAMPLES - 361 gm (.795[#])

• SAMPLE INSERTION #2 - CONTAINER "B"

(MONDAY) 8:30am 12-8-80

4 - 15ml Corvac Samples
2 - 10ml Corvac Samples

• RECORD WEIGHT OF SAMPLES - 175 gm (.385[#])

• SAMPLE INSERTION #3 - CONTAINER "B"

(MONDAY) 6:18pm 12-8-80

ESA Experiment Simulation


• RECORD WEIGHT - (1.075[#])

• SAMPLE INSERTION #4 - CONTAINER "A"

(TUESDAY) 10:15am 12-9-80

22 - 15 ml Corvac Samples
2 - 10 ml Corvac Samples

• RECORD WEIGHT OF SAMPLES - 728 gm
(1.6035[#])




Insertion #1
 10 - 15ml Corvac samples
 2 - 10ml Corvac samples

Insertion #2
 22- 15ml Corvac samples
 2 - 10ml Corvac samples

PASSIVE GN₂ FREEZER
 SL-1 TEST TIMELINE

"A"


SAMPLE CONTAINER



PASSIVE GN2 FREEZER
SL-1 TEST TIMELINE

"B"


EXPERIMENT CONTAINER



PASSIVE GAS FREEZER THERMAL RESPONSE

DECEMBER, 1980

TEST UNIT: S/N 988-80
CONTAINER "A"



LAUNCH


NO 128541

INSECTION

BAKING

SAVING HOTLINE REMOVED

12-7-50



COMMENTS

GN₂ PASSIVE FREEZER
TEST # 4

12-9-80 CONTAINER "A" INSERTION #2

1010 CONTAINER OPENED AND SAMPLE HOLDER
REMOVED.

5- 15ml tubes & 2- 10ml tubes & spacers
fell out of bottom of rack and had to
be dumped from container

Tube inserted into bottom center space
blocked the retraction of the handle.
There is no way to distinguish the center
space to remain empty.

Bottom racks completely filled with tubes,
however, the top rack would not accept
the proper number of tubes. - If one
tube is put in the wrong location, they
will all be wrong.

Tubes were forced into the container and
container was closed. While working with
the tube holder, the top was placed on the
container.

When replacing the holder, again several
tubes fell out of the bottom and had to
be dumped out and reloaded.

1020 CONTAINER TOP SREWED ON

COMMENTS

GN₂ PASSIVE FREEZER
TEST #4

12-11-80

CONTAINER "A" SAMPLE HOLDER REMOVAL

1400

CONTAINER OPENED AND ATTEMPT TO
REMOVE SAMPLE HOLDER FAILED

- Tubes that were inserted 12-9-80 were jammed and would not allow removal of sample holder.
- Three tube were fished out of container which allowed removal of holder.
- It was noted that there were only 17 tubes on the lower portion which meant 19 tubes were forced into upper portion.

1410

Container top screwed back on

- All tubes removed were frozen and there was no breakage

COMMENTS

GN₂ PASSIVE FREEZER
TEST # 4

12-12-80 CONTAINER "B" EXPERIMENT HOLDER
REMOVAL

0900

• Internal temperatures at approximately -160°C
at time of removal

• It was noted by B. French that light gloves
are better for manipulating the ESA
experiment door than the large bulky
gloves.

• All tubes removed frozen - there was
one broken, ESA simulation removed
and the holder re-inserted into freezer

0905

• Container closed and top screwed back
on.

TO: B. French SE4	DATE: 3/10/81
FROM: G.W. Belshaw, Project Engineer	CONTRACT: NAS9-15629
SUBJECT: GN ₂ PASSIVE FREEZER THERMAL TESTING - January-February 1981	

Enclosed are the results of the GN₂ Passive Freezer thermal testing conducted during the period of January 27, 1981 to February 17, 1981. The purpose of the testing was to establish the level of vacuum in the freezer and determine the effect of the variation in this vacuum level on the LN₂ boil off rate of the freezer.

Also to be determined whether the vacuum integrity could be re-established to produce consistent boil off rates. During the testing the minimum time required for the initial LN₂ charging was also investigated.

Figure 1 presents the static weight loss of the freezer for the various vacuum conditions tested and Figure 2 presents a plot of the boil off rate as a function of vacuum level within the freezer.

Figure 3 presents the results of the LN₂ charge time estimation with the weight gain of the freezer.

Figures 4-8 present the static weight loss of the freezer from charging to depletion of LN₂.

A determination of the vacuum level in the container as manufactured showed the pressure to be in the 10⁻¹ torr range. By increasing the vacuum, no significant improvement in the boil off rate was noted. Both were approximately .048 lbs/hour.

Severe degradation of boil off rate was noted at pressures higher than 10⁻¹ torr, up to 2.78 lb/hour at ambient pressure as would be expected.

It was also noted that the static boil off rate increases from .048 lb/hour to .127 lb/hour with the removal of the foam cap.

From this testing it was determined that the vacuum level of 10^{-4} torr can be re-established in the GN_2 freezer without a great deal of difficulty. This will insure confidence in the consistent performance of the freezer.

The charging of the GN_2 freezer with LN_2 can be accomplished in a shorter period of time than previously used for testing. The freezer will absorb LN_2 for a period of approximately 1 1/2 hours and after that point the freezer weight remains stable.

The following test procedure timeline details the testing accomplished. Also included is the detailed weight loss records.

John Belshaw

GN₂ PASSIVE FREEZER
TEST PROCEDURE TIMELINE

Container S/N 988-80 NASA S/N 1003

° Determination of Vacuum Level in Freezer

January 26, 1981

GN₂ freezer connected to vacuum pump on Helium Leak detector - container valve closed.

Connecting lines evacuated to 10⁻⁴ torr range.

1500 Container valve opened and pressure rose to the 150-200 y level (.15-.2 torr).

Continued pumping and evacuating container to the 10⁻⁴ range for approximately 16 hours.

° Effect of Variation in Vacuum Level

January 27, 1981

0845 Pressure level at 1.3×10^{-4} torr

0900 Closed valve and disconnected container

0905 Container dry weight 14.52#

Began LN₂ charge

1005 Full weight 31.98# and poured off

1007 Empty weight 27.09# (12.57# LN₂ absorbed)

Note: In previous test (December, 1980) there was 12.91# LN₂ loaded during the 24 hour soak.

January 28, 1981

Static boil off continued.

January 29, 1981

0900 Boil off rate = 0.48 #/hr

26.9# @ 1200 1/27/81

24.74# @ 0900 1/29/81

2.16# LN₂ boil off in 45 hours

1005 The freezer cap was removed and container allowed to stand open until 1300.

1300 Boil off rate = .127 #/hr

23.72 - (23.79 - .44)/2.91667 hr

Styrofoam block + 44# weight placed over opening. Boil off rate = .085 #/hr

(23.29 - 22.95)/4 hours

1900 Cap replaced on freezer

January 30, 1981

0900 Boil off rate = .0471 #/hr

(23.88 - 23.22)/14 hours

The container was reconnected to the vacuum pump and verification that the vacuum level was still in the 10⁻⁴ range.

The valve was then removed, with slight difficulty and 1 atm

pressure in the container. The container was disconnected from the vacuum lines and allowed to stand for 30 minutes.

The estimate of the boil off rate was 2.78 #/hour during this period. The top of the container frosted over and a great deal of moisture condensing on the sides of the container.

1100 The valve was replaced with difficulty. There was wear noted on the seals.

The vacuum lines were connected and the vacuum level inside the container was re-established.

1300 Vacuum level of 500 microns in the container and disconnected

Recharged with LN_2 - Wet weight 32.65#

1530 LN_2 poured off - Empty weight 27.33#
(12.81# of LN_2 loaded)

Replaced cap.

1900 Boiloff rate - .89 #/hour
(27.33 - 24.21)/3.5 hours

At this point there was frost build up around the container top and the boil off rate rose to 2.08 #/hour by 2400.

The valve had developed a leak and the vacuum level was lost.

2400 Testing was terminated.

February 2, 1981

1500 The container was reconnected to the vacuum pump.

Valve seals were replaced.

Container allowed to pump overnight to bring vacuum level to the 10^{-4} range.

° Determination of Minimum Freezer Charge Time

February 3, 1981

0900 Vacuum level established and container disconnected from the vacuum pump.

0910 Begin LN_2 fill to determine the length of time required to fill the container (Figure 3).

All weights were recorded after filling with LN_2 and replacing the cover to attain a constant LN_2 level within the container.

1215 Container left full of LN_2 and allowed to stand.

° Static Freezer Boil Off

February 4, 1981

1000 Boil off rate - .0442 #/hr
(32.24# - 31.29#)/21.5 hours

1011 Container refilled with LN₂

1114 LN₂ poured off

At this point the container was allowed to stand until the LN₂
was depleted.


February 15, 1981

2200 Estimation of LN₂ depletion

February 17, 1981

0900 Termination of testing. The internal temperature at this point
was -141°F.

ORIGINAL PAGE IS
 OF POOR QUALITY



FREEZER INTERNAL PRESSURE - torr
 FIGURE 2

ChilBabian


ORIGINAL PAGE IS
OF POOR QUALITY

ENV PASSIVE FREEZER CHARGE TEST

CONTAINER HEIGHT - POUNDS


CONTAINER SNV 988-00
DRY WEIGHT 55 LBS
INITIAL TEMPERATURE 70°F


ALL WEIGHTS MEASURED AFTER
TAPPING WITH LIT. AND RECORDING
COVER TO WHICH CONSUME
LIVE (EVEN)




TIME
FEBRUARY 5, 1957
FIGURE 3

12-13-57





ORIGINAL PAGE IS
OF POOR QUALITY



TO: B. French, SE4	DATE: 3/10/81
FROM: G.W. Belshaw, Project Engineer	CONTRACT: NAS9-15629
SUBJECT: GN ₂ PASSIVE FREEZER THERMAL TEST - VIBRATION CERTIFICATION - March, 1981	

Enclosed are the results of the thermal response of the Passive GN₂ Freezer during the Vibration Certification Test conducted at Bldg. 15 during the period of February 26, 1981 to March 9, 1981.

Figures 1 through 4 present the locker/freezer weight loss as a function of time.

A major result of this testing was the dramatic increase in the freezer boil off rate when the freezer is oriented in the horizontal position. The boil off rate ranged from .25 #/hr to .32 #/hr in the horizontal position to .046 #/hr in the vertical position. This is due to the increased convective flow with the freezer vent holes to the side.


The vibration shock testing on all six axes of the freezer had no effect on the boil off rate of the freezer. The samples inserted into the experiment holder were frozen at the time of the landing vibration and showed no signs of breakage or dislocation during the vibration test.


The load cell device for the measurement of the locker/freezer weight was very sensitive to slight position changes on the load cell assembly. At the conclusion of the testing, the range of weights recorded by slight position changes ranged between 31.87# and 34.05#. It can be concluded from this that the load cell is not accurate for recording absolute weight, but for weight differentials with no repositioning of the article.

The samples remained in the freezer until 0830 3/10/81 and were removed still frozen. This was approximately 78 hours after LN₂ depletion.

Also included in this report is the detailed test procedure timeline and weight loss record.

G.W. Belshaw





TO: B. French/SE4	DATE: 9/22/81
FROM: G.W. Belshaw, Project Engineer	CONTRACT: NAS9-15629
SUBJECT: GN ₂ PASSIVE FREEZER FUNCTIONAL TESTING - August, 1981	

This report documents the testing conducted on the Passive GN₂ Freezer during the period of August 10, 1981 to September 2, 1981. The containers tested had been refurbished by Cryogenics Associates and modified to include a Schrader vacuum valve on each container. The containers were designated Container "A", serial number 1358-79 and Container "B", serial number 1359-79.

The same test procedure timeline was utilized as for prior testing including the appropriate sample insertions as per the SL-1 timeline. Figures 1 and 2 present the test procedures with mission timelines relative to the testing are shown in Figures 3 and 4. It should be noted that the staggered starting times for the two containers were used to facilitate sample insertion times.

G.W. Belshaw

TEST RESULTS

The results of the testing during this period is described in the following paragraphs with the two containers described separately. Figures 5 through 9 present the weight loss curves for Container "A" and Figures 10 and 11 show the weight loss for Container "B". The Appendix provides the weight record for the testing period.

CONTAINER "A"

Testing began August 10, 1981 with the initial weighing of Container "A" at 14.21 pounds. The container was then filled with LN₂ to begin charging. During this period, excessive frost buildup on the container exterior was noted. The container was topped off and allowed to stand overnight. During this period a boiloff rate of 0.22 lb/hr was noted (see Figure 5). The container was topped off several more times and LN₂ pouroff occurred at 1550 August 11. At this point the sample holder was inserted into the container. Weight loss remained significantly high at a value of approximately 0.24 lb/hr during the next 20 hours. At this point the boiloff was increasing until 0700, August 13 where it was noted that the LN₂ had been depleted. Further testing with this container was terminated at 1100.

The probable cause for this excessive boiloff rate in this container would be vacuum level in the container not sufficient enough to provide proper insulative properties. To determine this, plans were formulated to open the vacuum valve, re-evacuate the container and test again.

On August 18, the Schrader valve was removed from the container, and by the ease of removal, noted that there was very little vacuum in the container. Inspection of the O-Ring on the Schrader valve showed that the O-Ring was too small which did not provide a good seal in the container. The O-Ring was then replaced with a larger one.

Vacuum connections were then set up and on August 19, the container was evacuated to approximately 10⁻³ torr level. The Schrader valve was resealed and the container was again charged with LN₂ (see Figure 6-9). As done previously, the container was allowed to stand overnight, full of LN₂. Boiloff rate for this period was now 0.047 lb/hr.

At 0900, August 20, the LN₂ pouroff occurred and the container allowed to stand until August 31 at which time the LN₂ was depleted. The average boiloff rate for this period was 0.044 lb/hr.

From this it can be concluded that the Container "A", as received from Cryogenics Associates was constructed with a Schrader valve O-Ring seal that was too small, allowing for a loss of vacuum. Resealing the evacuation of the container then produced the acceptable boiloff rates.

CONTAINER "B"

Testing on Container "B" began August 12 with the initial container weighing 13.86 pounds. The container was filled with LN₂ and topped off until 1600 August 13, at which time the LN₂ was poured off (see Figure 10). Boiloff rate during this period was approximately 0.045 lb/hr.

August 17, there were two sample insertions as per the SL-1 timeline and as shown in Figure 11. At 0830 2-10 ml Corvac samples and 4-15 ml Corvac samples were inserted in the experiment holder. At 1830 the ESA simulation was also inserted. Boiloff rate after the insertion period was approximately 0.046 lb/hr through August 19 at which point the test was terminated.

The testing on this container was terminated early due to a commitment of a container for crew training. Container "A" had been designated for this purpose, however, with the Container "A" anomaly and further testing required, Container "B" had to be used for this purpose.

The data of Figure 11 was extrapolated to the end of mission (164 hr MET) and the container weight estimated at 16.3 pounds. This represents approximately 1.0 pounds of LN₂ remaining which would provide approximately 20 hours of freezer life beyond landing.

CONCLUSIONS

The testing of these two containers showed that by allowing the container to stand during charging, the boiloff rate for the containers can be verified in a short period of time to determine the freezing capability of the container. The primary cause for any degradation would be loss of vacuum which can be readily re-established. Acceptable boiloff rates should be in the 0.044 to 0.047 lb/hr range.

Container "A", as received from Cryogenics Associates, was constructed without a proper size Schrader valve O-Ring seal, which caused a loss of vacuum. Seal replacement and evacuation produced a container that would provide for mission requirements.

Container "B" performed as expected and maintained the samples and experiments for the duration of the mission.

FIGURE 1

GN₂ PASSIVE FREEZER TEST PROCEDURES

MISSION TIMELINE TEST

UNITS TO BE TESTED:

"A" Serial No. 1358-79

"B" Serial No. 1359-79

8/10/81

Prior to 4 pm

- Record container weight "A" with cover
Note: All weights include cover
- Fill container "A" with LN₂ until container is full.

- Record container weight

Every 1-2 hours as needed

- Refill container "A" with LN₂ to maintain LN₂ level within one inch of top.

8/11/81

4 pm

- Continue topping and recording weight
- Pour off LN₂ from container, replace cover and record weight.

Every 2-3 hours

- Record container weight until end of test.

8/12/81

Prior to 4 pm

- Record container weight "B" with cover.
- Fill container "B" with LN₂ until container is full.

- Record container weight.

Every 1-2 hours as needed

- Refill container "B" with LN₂ to maintain LN₂ level within one inch of top.

8/13/81

4 pm

- Continue topping and recording weight.

- Pour off LN₂ from container "B", replace cover and record weight

Every 2-3 hours

- Record container weight until end of test.

End of test estimated 8/24/81.

FIGURE 2
GN₂ PASSIVE FREEZER TEST PROCEDURES
MISSION TIMELINE TEST

° SAMPLE INSERTION #1 - CONTAINER "A"

8/13/81	9:15 am	10 - 15 ml Corvac Samples
		2 - 10 ml Corvac Samples

Weight of Samples - .795#

° SAMPLE INSERTION #2 - CONTAINER "B"

8/17/81	8:30 am	4 - 15 ml Corvac Samples
		2 - 10 ml Corvac Samples

Weight of Samples - .39#

° SAMPLE INSERTION #3 - CONTAINER "B"


8/17/81	6:18 pm	ESA Experiment Simulation
---------	---------	---------------------------

Weight of Sample - 1.09#

° SAMPLE INSERTION #4 - CONTAINER "A"

8/18/81	10:15 am	22 - 15 ml Corvac Samples
		2 - 10 ml Corvac Samples

Weight of Samples - (not recorded)



Insertion # 1 10 - 15 ml Corvac samples
2 - 10 ml Corvac samples


Insertion # 2 22 - 15 ml Corvac samples
2 - 10 ml Corvac samples

PASSIVE GN₂ FREEZER

SL-1 TEST TIMELINE

UNIT "A"

SAMPLE CONTAINER



Insertion 4 - 15 ml Corvac samples
2 - 10 ml Corvac samples

PASSIVE GN₂ FREEZER
SL-1 TEST TIMELINE

UNIT "B"

EXPERIMENT CONTAINER

WEIGHT - POUNDS

TIME - HOURS


TUBE WELDER INSERTED

BOILER DATE

WEIGHT

TIME - HOURS	WEIGHT - POUNDS
0	0
10	10
20	20
30	30
40	40
50	50
60	60
70	70
80	80
90	90
100	100

46 1513



SWEET 2

ALBERT EINSTEIN

REVIEW

64-85711-001 201235

100-443887-100

अथर्ववेदः

THE
FIRE
OF
THE
FIRE

—



DEFO

五

1957

五、

PRDO

[illegible]


PPV

4-20514

101-4512


ORIGINAL PAGE IS
OF POOR QUALITY

ORIGINAL PAGE IS
 OF POOR QUALITY



SHEET 4

ORIGINAL PAGE IS
 OF POOR QUALITY



18.1-1-5
 (MILITARY)

FIGURE 9

[illegible]

23475

MISS GAY

THE

[illegible]

朱子

TEST TEAMMATED & SAMPLES

2015/07 2015/08 2015/09 2015/10

76194-25101-199

1830 ESE Sample 740ms 755ms 770ms 785ms 800ms 815ms 830ms 845ms 860ms 875ms 890ms 905ms 920ms 935ms 950ms 965ms 980ms 995ms 1010ms 1025ms 1040ms 1055ms 1070ms 1085ms 1100ms 1115ms 1130ms 1145ms 1160ms 1175ms 1190ms 1205ms 1220ms 1235ms 1250ms 1265ms 1280ms 1295ms 1310ms 1325ms 1340ms 1355ms 1370ms 1385ms 1400ms 1415ms 1430ms 1445ms 1460ms 1475ms 1490ms 1505ms 1520ms 1535ms 1550ms 1565ms 1580ms 1595ms 1610ms 1625ms 1640ms 1655ms 1670ms 1685ms 1700ms 1715ms 1730ms 1745ms 1760ms 1775ms 1790ms 1805ms 1820ms 1835ms 1850ms 1865ms 1880ms 1895ms 1910ms 1925ms 1940ms 1955ms 1970ms 1985ms 2000ms 2015ms 2030ms 2045ms 2060ms 2075ms 2090ms 2105ms 2120ms 2135ms 2150ms 2165ms 2180ms 2195ms 2210ms 2225ms 2240ms 2255ms 2270ms 2285ms 2300ms 2315ms 2330ms 2345ms 2360ms 2375ms 2390ms 2405ms 2420ms 2435ms 2450ms 2465ms 2480ms 2495ms 2510ms 2525ms 2540ms 2555ms 2570ms 2585ms 2600ms 2615ms 2630ms 2645ms 2660ms 2675ms 2690ms 2705ms 2720ms 2735ms 2750ms 2765ms 2780ms 2795ms 2810ms 2825ms 2840ms 2855ms 2870ms 2885ms 2900ms 2915ms 2930ms 2945ms 2960ms 2975ms 2990ms 3005ms 3020ms 3035ms 3050ms 3065ms 3080ms 3095ms 3110ms 3125ms 3140ms 3155ms 3170ms 3185ms 3200ms 3215ms 3230ms 3245ms 3260ms 3275ms 3290ms 3305ms 3320ms 3335ms 3350ms 3365ms 3380ms 3395ms 3410ms 3425ms 3440ms 3455ms 3470ms 3485ms 3500ms 3515ms 3530ms 3545ms 3560ms 3575ms 3590ms 3605ms 3620ms 3635ms 3650ms 3665ms 3680ms 3695ms 3710ms 3725ms 3740ms 3755ms 3770ms 3785ms 3800ms 3815ms 3830ms 3845ms 3860ms 3875ms 3890ms 3905ms 3920ms 3935ms 3950ms 3965ms 3980ms 3995ms 4010ms 4025ms 4040ms 4055ms 4070ms 4085ms 4100ms 4115ms 4130ms 4145ms 4160ms 4175ms 4190ms 4205ms 4220ms 4235ms 4250ms 4265ms 4280ms 4295ms 4310ms 4325ms 4340ms 4355ms 4370ms 4385ms 4400ms 4415ms 4430ms 4445ms 4460ms 4475ms 4490ms 4505ms 4520ms 4535ms 4550ms 4565ms 4580ms 4595ms 4610ms 4625ms 4640ms 4655ms 4670ms 4685ms 4700ms 4715ms 4730ms 4745ms 4760ms 4775ms 4790ms 4805ms 4820ms 4835ms 4850ms 4865ms 4880ms 4895ms 4910ms 4925ms 4940ms 4955ms 4970ms 4985ms 5000ms 5015ms 5030ms 5045ms 5060ms 5075ms 5090ms 5105ms 5120ms 5135ms 5150ms 5165ms 5180ms 5195ms 5210ms 5225ms 5240ms 5255ms 5270ms 5285ms 5300ms 5315ms 5330ms 5345ms 5360ms 5375ms 5390ms 5405ms 5420ms 5435ms 5450ms 5465ms 5480ms 5495ms 5510ms 5525ms 5540ms 5555ms 5570ms 5585ms 5600ms 5615ms 5630ms 5645ms 5660ms 5675ms 5690ms 5705ms 5720ms 5735ms 5750ms 5765ms 5780ms 5795ms 5810ms 5825ms 5840ms 5855ms 5870ms 5885ms 5900ms 5915ms 5930ms 5945ms 5960ms 5975ms 5990ms 6005ms 6020ms 6035ms 6050ms 6065ms 6080ms 6095ms 6110ms 6125ms 6140ms 6155ms 6170ms 6185ms 6200ms 6215ms 6230ms 6245ms 6260ms 6275ms 6290ms 6305ms 6320ms 6335ms 6350ms 6365ms 6380ms 6395ms 6410ms 6425ms 6440ms 6455ms 6470ms 6485ms 6500ms 6515ms 6530ms 6545ms 6560ms 6575ms 6590ms 6605ms 6620ms 6635ms 6650ms 6665ms 6680ms 6695ms 6710ms 6725ms 6740ms 6755ms 6770ms 6785ms 6800ms 6815ms 6830ms 6845ms 6860ms 6875ms 6890ms 6905ms 6920ms 6935ms 6950ms 6965ms 6980ms 6995ms 7010ms 7025ms 7040ms 7055ms 7070ms 7085ms 7100ms 7115ms 7130ms 7145ms 7160ms 7175ms 7190ms 7205ms 7220ms 7235ms 7250ms 7265ms 7280ms 7295ms 7310ms 7325ms 7340ms 7355ms 7370ms 7385ms 7400ms 7415ms 7430ms 7445ms 7460ms 7475ms 7490ms 7505ms 7520ms 7535ms 7550ms 7565ms 7580ms 7595ms 7610ms 7625ms 7640ms 7655ms 7670ms 7685ms 7700ms 7715ms 7730ms 7745ms 7760ms 7775ms 7790ms 7805ms 7820ms 7835ms 7850ms 7865ms 7880ms 7895ms 7910ms 7925ms 7940ms 7955ms 7970ms 7985ms 8000ms 8015ms 8030ms 8045ms 8060ms 8075ms 8090ms 8105ms 8120ms 8135ms 8150ms 8165ms 8180ms 8195ms 8210ms 8225ms 8240ms 8255ms 8270ms 8285ms 8300ms 8315ms 8330ms 8345ms 8360ms 8375ms 8390ms 8405ms 8420ms 8435ms 8450ms 8465ms 8480ms 8495ms 8510ms 8525ms 8540ms 8555ms 8570ms 8585ms 8600ms 8615ms 8630ms 8645ms 8660ms 8675ms 8690ms 8705ms 8720ms 8735ms 8750ms 8765ms 8780ms 8795ms 8810ms 8825ms 8840ms 8855ms 8870ms 8885ms 8900ms 8915ms 8930ms 8945ms 8960ms 8975ms 8990ms 9005ms 9020ms 9035ms 9050ms 9065ms 9080ms 9095ms 9110ms 9125ms 9140ms 9155ms 9170ms 9185ms 9200ms 9215ms 9230ms 9245ms 9260ms 9275ms 9290ms 9305ms 9320ms 9335ms 9350ms 9365ms 9380ms 9395ms 9410ms 9425ms 9440ms 9455ms 9470ms 9485ms 9500ms 9515ms 9530ms 9545ms 9560ms 9575ms 9590ms 9605ms 9620ms 9635ms 9650ms 9665ms 9680ms 9695ms 9710ms 9725ms 9740ms 9755ms 9770ms 9785ms 9800ms 9815ms 9830ms 9845ms 9860ms 9875ms 9890ms 9905ms 9920ms 9935ms 9950ms 9965ms 9980ms 9995ms 10010ms 10025ms 10040ms 10055ms 10070ms 10085ms 10100ms 10115ms 10130ms 10145ms 10160ms 10175ms 10190ms 10205ms 10220ms 10235ms 10250ms 10265ms 10280ms 10295ms 10310ms 10325ms 10340ms 10355ms 10370ms 10385ms 10400ms 10415ms 10430ms 10445ms 10460ms 10475ms 10490ms 10505ms 10520ms 10535ms 10550ms 10565ms 10580ms 10595ms 10610ms 10625ms 10640ms 10655ms 10670ms 10685ms 10700ms 10715ms 10730ms 10745ms 10760ms 10775ms 10790ms 10805ms 10820ms 10835ms 1085

(1) 7-15-71 7-15-71
7-15-71 7-15-71
7-15-71 7-15-71

SECRET - EYES ONLY

11

THE